Technical Data Sheet

V-TWIN MINERAL

HIGH PERFORMANCE 4-STROKE ENGINE OIL

DESCRIPTION:

Mineral based 4-stroke engine oil specifically formulated for V-Twin engines. Shear-stable formulation provides excellent film thickness and viscosity stability across all operating temperatures. Advanced, proprietary additive system with industry leading extreme pressure and anti-wear protection keeps your engine running clean, trouble-free and extends the life of the machine. Exceeds the requirements of API SN PLUS / JASO MA2.

FEATURES & BENEFITS:

- Formulated specifically for V-Twin engines
- Superior protection at any temperature
- Excellent clutch feel and clutch protection
- Shear stable formula maintains oil viscosity and film thickness
- Optimizes cleanliness while controlling oxidation and wear
- Exceeds API SN PLUS and JASO MA2 specifications

APPLICATIONS:

For all air and water-cooled V-Twin 4-stroke gasoline engines.

TECHNICAL DATA

SPECIFICATION	TEST METHOD	10W-40	20W-50	25W-60	50WT	60WT	70 WT
APPEARANCE	VISUAL	Amber	Amber	Amber	Amber	Amber	Amber
VISCOSITY @ 40°C (cSt)	D445	90.3	165.2	240.5	186.6	298.0	373.9
VISCOSITY @ 100°C (cSt)	D445	13.5	18.6	23.6	18.0	24.6	28.2
VISCOSITY INDEX	D2270	151	126	122	105	105	103
FLASH POINT (°C)	D92	220	228	248	248	257	250
POUR POINT (°C)	D97	-39	-36	-24	-27	-18	-12
DENSITY @ 15 °C (g/ml)	D4052	0.867	0.875	0.884	0.898	0.894	0.869

Maxima Racing Oils 9266 Abraham Way • Santee, CA 92071 USA **Phone** +1 (619)-449-5000 **Fax** +1 (619)-619-9694 **Web** www.MaximaUSA.com